

### Electrical Connection

Pre-Wired

Cable: PVC 4 x 0,75 mm<sup>2</sup>

Length: 1 m.

(Different cables or lengths, page 13)

### Operating Head Type



**G45 - Ø 18 nylon roller lever**



**G51 - Adjustable lever with Ø 18 nylon roller**



**G5100 - Adjustable toothed lever (step 2 mm) with Ø 18 nylon roller**

Conformity /  (N.C. contact with positive opening operation)			
Max actuation speed [m/s]	1,5	1,5	1,5
Min. force [N] or torque [Nm]: actuation / positive opening operation	0,08 / 0,28	0,08 / 0,28	0,08 / 0,28

### Additional Technical Datas

<b>Z</b> Snap Action Contacts (1NO + 1NC)		<b>Order Code</b>	<b>EP2G45Z</b>	<b>EP2G51Z</b>	<b>EP2G5100Z</b>
		Operation Diagram			
<b>X</b> Non overlapping Slow Action Contacts (1NO + 1NC)		<b>Order Code</b>	<b>EP2G45X</b>	<b>EP2G51X</b>	<b>EP2G5100X</b>
		Operation Diagram			

<b>Weight (packing per unit)</b>	<b>[kg]</b>	<b>0,180</b>	<b>0,190</b>	<b>0,190</b>
----------------------------------	-------------	--------------	--------------	--------------

### Dimensions (in mm)

